



Part Number	AWG	mm <sup>2</sup>	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
950014 - (Colour Code)	14	2.5	0.145	3.7	20.6

**Recommended Applications:**

This hook-up wire is <HAR>, CSA, UL approved for use in the North American and European markets. This product can be used in electronic equipment, medical equipment, electrical appliances and many other applications for products being used in the North American and European markets.

**Minimum Bend Radius:**

For installation only 4 x cable diameter

**Temperature Range:**

<HAR> -40C to + 70C  
CSA/UL -40C to +105C

**Nominal Voltage Rating:**

H05V-K <HAR> 300/500V, H07V-K <HAR> 500/750V  
CSA/UL 600V

**Test Voltage:**

H05V-K 2000V, H07V-K 2500V

**Colour Code:**

00 – Green / Yellow	01- Black	02 – Blue	03 – Brown	04 - Red
05 – White	06 - Grey	07 - Violet	08 – Pink	09 - Orange
10 – Yellow	11 – Green	14 – Dark Blue	16 – Light Blue	

**Approvals:**

<HAR>, UL, MTW or AWM STYLE 1015, VM-1, CSA TEW, 105C, 600V, FT1, CE  
RoHS compliant  
Conforms to CE low voltage directive

**Basic Construction:**

Fine wire to VDE 0295, class 5  
Tinned copper

**Insulating Compound:**

Specially formulated PVC

1.888.668.3539

289.337.9500

flex@awpinc.com

