



## HF210SD High Flex Shielded Data Cable



HF210SD CABLE AWP PT #210 240 2SD



Part Number	Stranding	Conductor	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
2102402SD	24AWG (Class 6 Stranding) Bare Copper	2	0.173	4.40	19

### **Recommended Applications:**

Continuous flexing, cable carrier, robotic flexing, automated material handling equipment and other flexing applications.

### **Basic Construction:**

Extra fine bare copper strands Class 6

### **Insulating Compound:**

Specially formulated PVC

### **Colour Code:**

DIN 47100

### **Shielding:**

Tinned copper braid 85% minimum coverage

### **Jacketing Compound:**

Specially formulated oil resistant black PVC

### **Resistant to:**

UV, oils, coolants, fuels, chemicals, water and abrasion  
Suitable for extremely harsh environments

### **Minimum Bend Radius:**

5 x cable diameter in flexing applications  
3 x cable diameter in static applications

### **Temperature Range:**

For static applications -40C to +80C  
For flexing applications -5C to +80C

### **Nominal Voltage Rating:**

300V

### **Test Voltage:**

3000V

### **Approvals:**

80C, 300V, CSA, UL, AWM I/II, A/B, CE, FT1  
RoHS compliant  
Conforms to CE low voltage directive

1.888.668.3539

289.337.9500

flex@awpinc.com

**CABLE AS FLEXIBLE AS OUR PEOPLE**