

# **Harmonized Hook-Up Wire**

H05V-K HAR/CE CABLE AWP PT #910020-00

# 

| Part Number           | AWG | mm <sup>2</sup> | Nominal Outer<br>Diameter (inches) | Nominal Outer<br>Diameter (mm) | Weight<br>Lb/1000ft |
|-----------------------|-----|-----------------|------------------------------------|--------------------------------|---------------------|
| 910020- (Colour Code) | 20  | 0.5             | 0.088                              | 2.20                           | 6                   |

## **Recommended Applications:**

This hook-up wire is <HAR> approved. This wire conforms to European standards. This product is ideal for use in switch gear cabinets, electronic equipment, medical equipment and many other applications for products being exported to Europe.

#### Minimum Bend Radius:

For installation only 4 x cable diameter

# **Temperature Range:**

<HAR> -30C to + 80C

#### Nominal Voltage Rating:

H05V-K <HAR> 300/500V, H07V-K <HAR> 500/750V

#### **Test Voltage:**

H05V-K 2000V, H07V-K 2500V

## Colour Code:

| 00 – Green / Yellow | 01- Black  | 02 – Blue      | 03 – Brown      | 04 - Red    |
|---------------------|------------|----------------|-----------------|-------------|
| 05 – White          | 06 - Grey  | 07 - Violet    | 08 – Pink       | 09 - Orange |
| 10 – Yellow         | 11 – Green | 14 – Dark Blue | 16 – Light Blue |             |

# Approvals:

CE, <HAR>, <VDE> RoHS compliant Conforms to CE low voltage directive

#### **Basic Construction:**

Fine wire to VDE 0295, class 5 Bare copper

#### Insulating Compound:

Specially formulated PVC

| 1.888.668.3539 | 289.337.9500 | flex@awpinc.com |
|----------------|--------------|-----------------|
|                |              |                 |

# CABLE AS FLEXIBLE AS OUR PEOPLE