



## SF410SD Super Flex Shielded Data Cable



SF410SD CABLE AWP PT #4102204SD



Part Number	Stranding	Conductor	Nominal Outer Diameter (inches)	Nominal Outer Diameter (mm)	Weight Lb/1000ft
4102204SD	22AWG Class 6 Bare Copper	4	0.208	5.30	25

### **Recommended Applications:**

Robotic applications, high speed cable carrier, automated handling equipment, pick and place robots, gantry robots, many high speed applications, tight bend radius applications. This is a small outer diameter cable capable of a tight bend radius.

### **Basic Construction:**

Extra fine bare copper strands Class 6

### **Insulating Compound:**

Specially formulated PP

### **Colour Code:**

DIN 47100

### **Shielding:**

Tinned copper braid 85% minimum coverage

### **Jacketing Compound:**

Specially formulated PUR

### **Resistant to:**

UV, oils, coolants, fuels, chemicals, water and abrasion  
Suitable for extremely harsh environments

### **Minimum Bend Radius:**

5 x cable diameter in flexing applications  
3 x cable diameter in static applications

### **Temperature Range:**

For static applications -50C to +80C  
For flexing applications -40C to +80C

### **Nominal Voltage Rating:**

300V

### **Test Voltage:**

3000V

### **Approvals:**

80C, 300V, CSA, UL, AWM I/II, A/B, CE, FT1  
RoHS compliant  
Conforms to CE low voltage directive



1.888.668.3539

289.337.9500

flex@awpinc.com

**CABLE AS FLEXIBLE AS OUR PEOPLE**